

LEDONARDO 2

LED LIGHT ENGINE FOR DESISTI LEDONARDO 2 KW

Bring new life to your the Leonardo by replacing the old power inefficient tungsten lamp with the more up to date LED technology. Ledonardo 2 is available in two correlated color temperatures comparable to tungsten (warm) and discharge (cold).



Powersaving - Long lamp life - Reliability - Smooth dimming

SPECIFICATIONS

POWER:

Switchmode power supply
AC Power: 100 – 240 V nominal, 50/60 Hz
Max. power consumption: 122 W.
Standby power: 5 W.
1,1 Amp @ 110V / 0,5 Amp @ 240V
Powercon IN
Ambient operating temperature: 0-40°C / 0-104°F
Ultra silent pulse fan assisting the large heatsink when needed.

LAMP:


High quality Cold LED array, CRI min. 90
High quality Warm LED array, CRI min. 90

CONTROL:

DMX512
DMX IN and DMX out for daisy chaining
8/16bit dimming 0-100%
1 or 3 control channels at 8bit / 2 or 4 channels at 16bit
Digital display
Ultra fast strobe channel

DIMENSIONS:(When mounted on Leonardo 2k)

Additional width: 0mm/0"
Additional height: 7mm/0,28"
Addiotional depth: 0mm/0"
Additional weight: 1,2kg/2,7lbs



In compliance with the RoHS and WEEE directives.

In compliance with EMC standards: EN 55103-1 & EN 55103-2: EN 55022, EN 55103-1 Annex A, EN 55022, EN 61000-3-2, EN 61000-3-3, EN 55103-1, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 55103-1 Annex B, EN 55103-1 Annex A, EN 61000-4-11

TEL.:+45 70 27 42 41 - MAIL: BROTHERS@BROTHERS-SONS.DK

WWW.BROTHERS-SONS.DK

BROTHER, BROTHER & SONS ApS

