



MSR Hot Restrike

MSR 575 HR 1CT/4

Thanks to an optimized color temperature and a high color rendering index, the MSR Hot Restrike creates perfect 'daylight' in any condition. Also, the single ended lamp design enables hot re-ignition, which ensures daylight lighting and superb color rendition is always instantly available. They also incorporate the innovative P3 technology, developed by Philips, which allows use at higher temperatures and therefore extends lifetime and consistency of high-quality light output.


Product data

General Information		Ignition Supply Voltage (Min)	
Cap-Base	G22 [G22]		207 V
Operating Position	UNIVERSAL [Any or Universal (U)]	Controls and Dimming	
Main Application	Studio/Theatre	Dimmable	Yes
Life To 50% Failures (Nom)	1000 h	Mechanical and Housing	
System Description	Hot Restrike	Cap-Base Information	-
Light Technical		Luminaire Design Requirements	
Color Code	- [Not Specified]	Bulb Temperature (Max)	700 °C
Luminous Flux (Min)	40000 lm	Pinch Temperature (Max)	350 °C
Luminous Flux (Nom)	49000 lm	Product Data	
Chromaticity Coordinate X (Nom)	323	Full product code	871829122105000
Chromaticity Coordinate Y (Nom)	328	Order product name	MSR 575 HR 1CT/4
Correlated Color Temperature (Nom)	6000 K	EAN/UPC - Product	8718291221050
Luminous Efficacy (rated) (Nom)	85 lm/W	Order code	928097705115
Color Rendering Index (Nom)	90	Numerator - Quantity Per Pack	1
Operating and Electrical		Numerator - Packs per outer box	4
Power (Rated) (Nom)	575 W	Material Nr. (12NC)	928097705115
Lamp Current (Nom)	6.95 A		

MSR Hot Restrike

Net Weight (Piece)	0.100 kg
--------------------	----------

Dimensional drawing



MSR 575 HR

Product	D	O	L	L	L	C	F	F	F
MSR 575 HR	30 mm	7.0 mm	69 mm	71 mm	70 mm	145 mm	43 mm	42 mm	41 mm
1CT/4									

