



MSR Gold™ MiniFastFit (Touring/Stage)

MSR Gold™ 700/2 MiniFastFit 1CT/4

Thanks to the specially designed lamp base, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity.

Product data


General Information		Operating and Electrical	
Cap-Base	PGJX28 [PGJX28]	Power (Rated) (Nom)	700 W
Operating Position	UNIVERSAL [Any or Universal (U)]	Lamp Current (Nom)	10.2 A
Main Application	Entertainment	Ignition Supply Voltage (Min)	198 V
Life To 50% Failures (Nom)	750 h	Controls and Dimming	
System Description	MiniFastFit	Dimmable	Yes
Light Technical		Mechanical and Housing	
Color Code	2	Cap-Base Information	PGJX28
Luminous Flux (Min)	44000 lm	Luminaire Design Requirements	
Luminous Flux (Nom)	47000 lm	Bulb Temperature (Max)	950 °C
Chromaticity Coordinate X (Nom)	300	Pinch Temperature (Max)	500 °C
Chromaticity Coordinate Y (Nom)	324	Product Data	
Correlated Color Temperature (Nom)	7200 K	Full product code	871829122117300
Luminous Efficacy (rated) (Nom)	69 lm/W		
Color Rendering Index (Nom)	75		

MSR Gold™ MiniFastFit (Touring/Stage)

Order product name	MSR Gold™ 700/2 MiniFastFit 1CT/4
EAN/UPC - Product	8718291221173
Order code	928199905115
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

Material Nr. (12NC)	928199905115
Net Weight (Piece)	0.052 kg

Dimensional drawing



Product	D	O	L	L	L	C	F	F	F
MSR Gold™	23.2	3.8	55	57	56	112	36.5	36	35.3
700/2 MiniFastFit	mm	mm	mm	mm	mm	mm	mm	mm	mm
1CT/4									

MSR GOLD 700/2 MiniFastFit

