



Contact Gantom

MAIN PHONE | 661-347-0779

CALIFORNIA OFFICE 25060 Avenue Stanford, Suite 115 Valencia, CA 91355

FLORIDA OFFICE 7091 Grand National Drive, Suite 103 Orlando, FL 32819

GENERAL INQUIRIES | sales@gantom.com

QUOTES/PRICING | quotes@gantom.com

PURCHASE ORDERS | orders@gantom.com


TECHNICAL SUPPORT | support@gantom.com

ACCOUNTING | accounting@gantom.com

SCAN HERE



Schedule a online product demonstration



GANTOM ONE UP

Building off the success of the Gantom One, the One Up brings four-color output to this LED pin spot and delivers a tight and punchy beam that produces homogeneous color mixing, even at close distances.

Featuring a native 4.5 degree beam angle, the Gantom One Up includes 4 diffusion filters, hex louver, and optional top hat, half hat, and angled cowlings for easy control over the beam. Its native DMX control and balanced dimming curve make it perfect for even the most demanding of lighting designers.

Whether you're illuminating a small space or a large venue, the Gantom One Up has everything you need to create stunning lighting designs.



scan for product page

PRECISION CP-7



The Precision CP-7 offers precise RGB control with its 7 channel DMX profile and features smooth dimming, variable strobing, color macros, and flicker effects.

This fixture comes bare wire and includes adapters for power and programming allowing for flexibility in permanent and seasonal installations.

With minimal maintenance required and over 50,000-hour lamp life expectancy, this fixture will hold strong through your installations year after year.



scan for product page

GANTOM TRACK

Gantom Track fixtures are now compatible with A.A.G Stucchi track.

Stucchi offers a wide range of products, giving lighting designers more options and flexibility to create stunning designs for their upcoming projects.

For more information on Gantom Track products, please contact us at sales@gantom.com.



FIXTURE UPDATES

- Redesign of all 60mm fixtures
- New beam control accessories and threaded retaining ring for 60mm fixtures
- Weatherproof ingress protection kit accessory for 60mm fixtures
- Gantom DMX V2 now IP67 rated
- 90+ CRI for all fixtures with color temperatures 3000k and below





PRECISION SERIES

PRECISION ALPHA Micro Pinspot





Multi-use spotlight with adjustable angle, brightness, and color with included filters

> **OPTICS** Beam 13° / Field 28°

ILLUMINANCE 843 lx (78.3 fc) @ 1 Meter

DIMENSIONS 71mm x 34mm x 27mm 2.80" x 1.34" x 1.06"

LED COLOR





Adjustable with Gel Filters

POWER 1.5 watts

IP RATING IP65

PRECISION Z SPOT Micro Spotlight





Single color high intensity fixture with far throw and intense color

> **OPTICS** Beam 11° / Field 32°

ILLUMINANCE 883 lx (82.0 fc) @ 1 Meter

DIMENSIONS 42mm x 40mm x 50mm 1.65" x 1.57" x 1.96"

LED COLOR



POWER 1.5 watts

IP RATING IP65

PRECISION Z FLOOD Micro Foodlight





Single color wide beam angle fixture for highlights and area color mixing washes

> OPTICS Beam 62° / Field 84°

ILLUMINANCE 66lx (6.1 fc) @ 1 Meter

DIMENSIONS 42mm x 40mm x 50mm 1.65" x 1.57" x 1.96"

LED COLOR









POWER 1.5 watts

IP RATING IP65



Z DMX SPOT Micro DMX Spotlight





Single color DMX dimmable fixture with intense color and throw distance.

OPTICS Beam 11° / Field 32°

ILLUMINANCE 883 lx (82.0 fc) @ 1 Meter

DIMENSIONS 42mm x 40mm x 50mm 1.65" x 1.57" x 1.96"

LED COLOR





POWER 1.5 watts

IP RATING IP65

Z DMX FLOOD Micro DMX Floodlight





DMX controlled micro flood fixture that produces even color washes.

OPTICS Beam 62° / Field 84°

ILLUMINANCE 66lx (6.1 fc) @ 1 Meter

DIMENSIONS 42mm x 40mm x 50mm 1.65" x 1.57" x 1.96"

LED COLOR





POWER 1.5 watts

IP RATING IP65

PRECISION CP-7 RGB DMX FX Light





RGB color mixing fixture with strobe light features and built in special effect macros

OPTICS Beam 18° - Soft Edge Beam

ILLUMINANCE 534lx (49.6 fc) @ 1 Meter

DIMENSIONS 42mm x 40mm x 50mm 1.65" x 1.57" x 1.96"

LED COLOR







POWER
3.3 watts
12 Volt DC Power ONLY

IP RATING
IP60
Indoor Use Only



GANTOM SERIES

Gantom iQ Gobo Projector





Micro LED gobo projector with zoomable lens

OPTICS 25° to 40° Adjustable zoom lens

ILLUMINANCE 510 lx (47.4 fc) @ 1 Meter

DIMENSIONS 94mm x 49mm x 50mm 3.7" x 1.93" x 1.97"

LED COLOR





POWER 2.8 watts

IP RATING IP40 IP65 with FA30 Accessory

Gantom Juni Framing Gobo Projector





The smallest framing projector in the world with sharp optics and precise focus adjustments

OPTICS 25° to 38° - Standard Lens 40° to 60° - Wide Lens

ILLUMINANCE 1620 lx (515 fc) @ 1 Meter

DIMENSIONS 129mm x 89mm x 79mm 5.08" x 3.50" x 3.11"

LED COLOR





POWER
9 watts
12 Volt DC Power ONLY

IP RATING
IP50
Indoor Use ONLY

Gantom One Compact Pinspot





LED pinspot with ultra narrow beam optics and included diffusion lenses

OPTICS
Beam 2.7° / Field 4.5°
Diffusible with included filters

ILLUMINANCE 22100lx (2053.2 fc) @ 1 Meter

DIMENSIONS 42mm x 40mm x 50mm 1.65" x 1.57" x 1.96"

LED COLOR







UV fixtures are made to order

POWER 4.8 watts

IP RATING
IP65
IP67 with FA47 Accessory

Gantom iQx DMX Gobo Projector





Micro LED gobo projector with zoomable lens and effect macros

> OPTICS 25° to 40° Adjustable zoom lens

ILLUMINANCE 510 lx (47.4 fc) @ 1 Meter

DIMENSIONS 94mm x 49mm x 50mm 3.7" x 1.93" x 1.97"

LED COLOR





POWER 2.8 watts

IP RATING IP40 IP65 with FA30 Accessory

Gantom Juni DMX DMX Framing Gobo Projector





Small DMX controlled framing projector with sharp optics and precise focus adjustments

OPTICS 25° to 38° - Standard Lens 40° to 60° - Wide Lens

ILLUMINANCE 1620 lx (515 fc) @ 1 Meter

DIMENSIONS 129mm x 89mm x 79mm 5.08" x 3.50" x 3.11"

LED COLOR





POWER 9 watts

IP RATING
IP50
Indoor Use ONLY

Gantom One DMX DMX Compact Pinspot





DMX controlled LED pinspot with ultra narrow beam optics in a compact formfactor

OPTICS
Beam 2.7° / Field 4.5°
Diffusible with included filters

ILLUMINANCE 22100lx (2053.2 fc) @ 1 Meter

DIMENSIONS 42mm x 40mm x 50mm 1.65" x 1.57" x 1.96"

LED COLOR







UV fixtures are made to order

POWER 4.8 watts

IP RATING IP65 IP67 with FA47 Accessory



GANTOM SERIES

Gantom One Up DMX RGBW Pinspot





RGBW color mixing ultra narrow beam pinspot fixture with DMX dimming

OPTICS
Beam 4.5° / Field 12.7°
Diffusible with included filters

ILLUMINANCE 17284 lx (1603.4 fc) @ 1 Meter

DIMENSIONS 88mm x 60mm x 60mm 3.35" x 2.36" x 2.36"

LED COLOR









POWER 5.5 watts

IP RATING IP65 IP67 with FA47 Accessory

DMX V2 RGBW **RGBW** Spotlight





Compact DMX spotlight with smooth dimming and RGBW color mixing

OPTICS Beam 16° / Field 32° Diffusible with included filters

ILLUMINANCE 883 lx (82 fc) @ 1 Meter

DIMENSIONS 58mm x 49mm x 63mm 2.28" x 1.93" x 2.48"

LED COLOR









POWER 4.8 watts

IP RATING **IP67**

DMX V2 DW Dynamic White Spotlight





Compact DMX spotlight with tunable white color temperature control

> **OPTICS** Beam 16° / Field 32° Diffusible with included filters

ILLUMINANCE 883 lx (82 fc) @ 1 Meter

DIMENSIONS 58mm x 49mm x 63mm 2.28" x 1.93" x 2.48"

LED COLOR





POWER 4.8 watts

IP RATING IP67



Gantom 7 7 Color DMX Spotlight





Versatile fixture with full color and beam control designed to handle all theatrical lighting needs

OPTICS
Beam 15° / Field 35°
Diffusible with included filters

ILLUMINANCE 650 lx (60.4 fc) @ 1 Meter

DIMENSIONS 88mm x 60mm x 60mm 3.35" x 2.36" x 2.36"

LED COLOR



POWER 7.5 watts

IP RATING
IP65
IP67 with FA47 Accessory

Gantom R4 RGBW DMX RGBW Recessed Light





Compact recessed fixture with adjustable optics, smooth dimming, and excellent color mixing

OPTICS
Beam 16° / Field 32°
Diffusible with included filters

ILLUMINANCE 883 lx (82 fc) @ 1 Meter

DIMENSIONS 70mm x 55mm x 40mm 2.76" x 2.17" x 1.57"

LED COLOR



POWER 4.8 watts

IP RATING
IP60
Indoor Use ONLY

Gantom R4 DW Dynamic White Recessed Light





Compact recessed fixture with adjustable optics, smooth dimming, and tunable color temperature

OPTICS
Beam 16° / Field 32°
Diffusible with included filters

ILLUMINANCE 883 lx (82 fc) @ 1 Meter

DIMENSIONS 70mm x 55mm x 40mm 2.76" x 2.17" x 1.57"

LED COLOR



POWER 4.8 watts

IP RATING
IP60
Indoor Use ONLY



SYSTEM COMPONENTS

GP002 Indoor/Outdoor Field Install Distribution Box



Designed to fit your application, this G8 Distribution Box allows you to tailor your Gantom Pro Cable system to you needs

DIMENSIONS :

204mm x 200mm x 92mm

8.03" x 7.87" x 3.62"

POWER INPUT

12-24VDC, 5A maximum

IP RATING

IP67

COMPATIBLE COMPONENTS

Branch Cables:

CB141, CB138, CB132, CB133,

CB134

Power Supplies: PP33, PP35

GP003 Indoor Plug-and-Play Distribution Box



Quick and easy to set up, the Plug-and-Play G8 makes Pro Cable quick and secure to use

DIMENSIONS

200mm x 94mm x 65mm

7.87" x 3.70" x 2.56

POWER INPUT

12-24VDC, 5A maximum

IP RATING

IP40

COMPATIBLE COMPONENTS

Branch Cables:

CB139, CB130, CB131

Power Supplies: PP31, PP33, PP35

GP004 Indoor/Outdoor Plug-and-Play Distribution Box



The power of the G8
Distribution Box with the versatility of Trunk Cable Compatible with T Connectors and related accessories

DIMENSIONS

200mm x 94mm x 65mm

7.87" x 3.70" x 2.56

POWER INPUT

12-24VDC, 7A maximum

IP RATING

IP60

IP65 with CB147 Caps

COMPATIBLE COMPONENTS

Trunk Cables:

CB129, CB120, CB121, CB122,

CB137

Branch Cables: CB139, CB130, CB131

Power Supplies: PP33. PP35. PP36

CB124 T Connector with Integrated DMX Repeater



Individual fixture power and data distribution with Trunk Cable connections allow for flexible system layouts

DIMENSIONS

119mm x 64mm x 24mm

4.67" x 2.50" x 0.94"

POWER INPUT

12-24VDC, 7A maximum

IP RATING

IP65

COMPATIBLE

Trunk Cables:

COMPONENTS CB129, CB120, CB121, CB122.

CB137

Branch Cables:

CB139, CB130, CB131

Power Supplies: PP33, PP35, PP36





PowerPak Mini 12 Watt1 Amp



INPUT OUTPUT 100-200 VAC 12VDC

PowerPak 5000 60 Watt 5 Amp



INPUT 100-265 VAC OUTPUT 12VDC

PowerPak Pro 60 Watt 5 Amp - IP67



INPUT 100-200 VAC OUTPUT 12VDC

PowerPak Max 200 Watt 8.33 Amp - IP67



INPUT 100-305 VAC OUTPUT 24VDC

PowerPak Plug & Play 60 Watt 5 Amp - DMX Injection



INPUT 100-277 VAC OUTPUT 24VDC

DarkBox Programmer V2 Standalone Programming Device



Simple and reliable way to configure the settings of Gantom fixtures.

FEATURES

Battery Operated USB C Charging Pro Cable Connector Easy to use Interface

SCAN TO LEARN MORE ABOUT GANTOM SYSTEMS



Pro Cable



Go Cable




















Have you used Gantom fixtures on a project recently?

We are looking for case studies to highlight our products in action! If you have something you are able to share, please email us at sales@gantom.com and tell us about your project.

We look forward to seeing what you have been working on.







www.gantom.com | sales@gantom.com 25060 Avenue Stanford, Suite 115, Valencia, CA 91355 Ph. [661] 347-0779