

CODA CYC

Date: _____

Type: _____

Firm Name: _____

Project: _____

The Coda Cyc is a high output theatrical cyc luminaire that provides rich color mixing for seamless coverage of a stage's cyclorama. The RGBALC (Red, Green, Blue, Amber, Lime & Cyan) color mixing system on the Coda Cyc offers rich colors using a wide mixable color spectrum, but it can be easily controlled with traditional CYM controls using the SmartColor Control system. With 2 zone color control, it is easy to create natural-looking split-color cyc coverage.



- High output LED cyc - modern theatrical cyc with quality you can trust.
- High CRI RGBALC Color System with SmartColor Control - wide range of vivid color options that can be programmed using CYM.
- Independent color mixing and temperature controls - match color palette to color temperature without manual adjustment for simpler programming.
- Two-zone color control - create natural looking split colors.

- Fanless design - perfect for use in quiet environments.
- Wide coverage per fixture - 2.5m (8.5ft) coverage @ 1.2m (4ft) from projection surface.
- Adjustable frequency to exceed camera frame rates - camera friendly fixtures for IMAG, event recordings, or TV & film applications.

For detailed product information, please refer to the Product Guide at <https://www.vari-lite.com/global/products/coda-led-cyc>



VARI*LITE

Specifications

Due to continuous improvements and innovations, specifications may change without notice.

Source

LED	Multichromatic Light Engine - RGBALC
Source Max Power Consumption	205W
LED Refresh Rate	12 Hz to 25kHz
Dimming	Electronic 16-bit
Dimmer Curves	Square Law (Default), Linear, S -Curve
Dimmer Control Option	Dimmer Snap On/Off On reduces auto dimmer smoothing
Strobe Speed	0 - 30Hz
Strobe Modes	Standard, Lightening, Random

Optical Performance

Beam Angle	40° x 60°
Output Lumens	Standard - 13,000
Smart Color CCT	1800 K to 10000 K
CRI RA	94
CRI R9	96
Tm30	Rf 88 / Rg 105

Color System

Color Mixing	RGBALC
Color Mixing Control	Smart Color, Open Source or Quick Color
Color Calibration	Selectable On/Off
Color Mixing Control Option	Color Snap On/Off On reduces auto smoothing color to create faster color changes
Variable CTO	1800 K to 10000 K (Smart Color Mode)
Color Presets	32 Calibrated Colors
User Definable Color Presets	20
Chromatic Aberration	Magenta / Green shift control

Electrical

Max output Power Consumption	223 W @ 120 V, 214 W @ 240 V
Power Connection	TrueOne Compatible - In / Thru Power cable not included - input connector only
Input Voltage	100–240 VAC, 50 / 60 Hz

Data

Supported Protocols	DMX512-A (RDM)
DMX Modes	
Smart Color Control (default)	13 / 23 Channels
Q Color Mode	4 Channels
Open Color Control	17 / 29 Channels
Data Connections	5 - Pin XLR Input and Thru
Zone Control	1 / 2 Zones
Manual Preset Mode	Advanced Feature local control

Noise Level / Fan Control

Cooling System Type	Convection Cooling - Fanless
---------------------	------------------------------


Mounting

Hanging Type	2 x 107mm Omega Bracket (Not Included)
Distance from Cyc	1.0 mm (4.0 in)
Fixture mounting/Hanging orientation	Hanging - Floor - Side
Secondary Safety Wire Point	1 x Safety point located on rear of fixture housing Safety Wire not included

Photometrics and IES Files

For IES files and photometric reports, please refer to the product page:
<https://www.vari-lite.com/global/products/coda-led-cyc>

Dimensions



Physical

Construction	Superstructure made of Aluminum, and steel metal plates, Covers Aluminum
IP Rating	IP20
Standard Finish	Black
Dimensions	335 x 508 x 326 mm (13.0 x 20.0 x 13.0 in)
Packed Dimensions	635 x 410 x 500 mm (25.0 x 16.0 x 20.0 in)
Fixture Weight	15.0 kg (33.0 lb)
Packed Weight	18.0 kg (40.0 lb)
Operating Temperature	0-40°C (32-104°F)

Certification and Safety

Approbations	CE, ETL, UL, FCC CSA, RoHS, ISO 9001
--------------	--------------------------------------

Luminaire and Accessories

Product type	Order Code
CODA CYC, Black	64509-001
Coda Cyc , 205w Multichromatic Light Engine - RGBALC, c/w Power input connector, Black	
Accessories	
Omega Bracket (2 Required per fixture NOT INCLUDED) Required for Hanging of fixture	3002000390
VL Omega Bracket , 1 x 107mm Bracket , compatible with VL800 PROPAR,EVENTPAR,EVENTWASH, CODA and AURORA),	



© 2024 Signify Holding. All rights reserved. All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Vari-Lite
<https://www.vari-lite.com/global/products/coda-led-cyc>