



Date
Project
Fixture
Comments

## Description

Compact, powerful, versatile... this is the One. Gantom listened to some of the most skilled lighting professionals in the industry, and based on their input, designed the Gantom One; the pinspot to rule all pinspots. Compared to a traditional 30W pinspot, the One runs cooler and safer on far less power, has much cleaner optics, and can even be run on batteries. The Gantom One includes an integrated, easy-to-use accessory mounting system, where you can choose from an array of glare control, color filters, and diffusers to achieve any effect you desire without tools or hassle.

Physical
L: 104mm (4.09") W: 60mm (2.36") H: 60mm (2.36")
Weight: .230kg / .51lbs
Black anodized aluminum
Power
.386a~.180a 12~24vdc CW .345a ~ .196a 12~24vdc
DC Barrel Connector Non-Weatherproof IP20 Length: 9" (22.8mm)
Installation
IP65 - Indoor / Outdoor Temporary*
IP67 - With FA47 Installed
*Do not use for outdoor applications where water can collect on lens without FA47.

Optics
2.7° Beam 4.5° Field
4pcs Assorted beam shaping filters included:
1 Notch: 9° / 18° 2 Notch: 27° / 51° 3 notch: 70° / 110°
Asymmetric U Notch: 18° / 32° short axis 47° / 84° long axis
<u>Warm White</u>
22100 lx (2053.2 fc) @ 1m 8100 lx ( 752.5 fc) @ 2m 4100 lx (380.9 fc) @ 3m
<u>Cool White</u>
15000 lx (1393.5 fc) @ 1m 5500 lx (511.0 fc) @ 2m 2700 lx (250.8 fc) @ 3m

Color Specifications	
White 3000K, Cool White 6500K, Ultraviolet (395nm)	
Variations	
Part #	Description
GP255B	Gantom One - Cool White -Pro Cable Connector -Hex Louver -DMX
GP256B	Gantom One - Warm White -Pro Cable Connector -Hex Louver -DMX
GP257B	Gantom One - UV - Pro Cable Connector -Hex Louver -DMX
GT51B	Gantom One - Cool White -2.1mm Barrel Connector* -Hex Louver - No DMX/PWM Dimming
GT51B	Gantom One - Cool White -2.1mm Barrel Connector* -Hex Louver - No DMX/PWM Dimming
GT52B	Gantom One - Warm White -2.1mm Barrel Connector* -Hex Louver - No DMX/PWM Dimming

Accessory Information	
Part #	Description
FA47	IP67 Plastic Cap & O-Rings for Gantom One, Gantom 7, and Gantom One Up "B" models
FA44	Top Hat / Snoot for Gantom One, Gantom 7, and Gantom One Up "B" model
FA45	Half Hat for Gantom One, Gantom 7, and Gantom One Up "B" models
FA46	Angled Cowling for Gantom One, Gantom 7, and Gantom One Up "B" model
RP34	Replacement Diffusion Filter Pack
DB32	DarkBox Programmer V2 - Required to set DMX address
PP21	PowerPak Mini (12V 1A Output, Input 100-240v~ 0.68A 50/60 Hz)

**Gantom One is backed by Gantom's two year warranty. Special orders and Stucchi track options available. Please contact Gantom at [sales@gantom.com](mailto:sales@gantom.com) for more information.**

