

# LEKOLEDOUTDOORPROFILE

# FULL COLOR

This document provides basic setup instructions and safety warnings for the following product(s):

64506-002

Leko LED Outdoor Profile Full Color

Read all instructions before installing or using this product. Retain this manual for future reference. Additional product information and descriptions may be found on the product specification sheet.




# INSTALLATION AND SETUP

# MOUNTING


The unit should be mounted via its screw holes on the bracket. Always ensure that the unit is firmly fixed to avoid vibration and slipping while operating. Always ensure that the structure to which you are attaching the unit is secure and is able to support a weight of 10 times of the unit's weight. Always use a safety cable that can hold up to 12 times the weight of the unit when installing the fixture.

The luminaire must be mounted by professionals.



# SET UP

# **Control Panel**



- (1) LCD display shows the menu and selected functions
- (2) MENU To select the programming functions
  DOWN To go backward in the selected functions
  UP To go forward in the selected functions
  ENTER To confirm the selected functions
- (3) DMX IN 5-pin XLR cable to link DMX console
- (4) DMX OUT 5-pin XLR cable to link to the next unit
- (5) Power In connects to power supply
- (6) Power Out connects to next fixture

1

# QUICK REFERENCE DMX MAPS

# SSCC MODE

| DMX<br>CHANNEL | PARAMETER         |
|----------------|-------------------|
| 1              | Intensity (High)  |
| 2              | Intensity (Low)   |
| 3              | Strobe            |
| 4              | Color Preset      |
| 5              | Zoom              |
| 6              | Focus (High)      |
| 7              | Focus (Low)       |
| 8              | Gobo Index (High) |
| 9              | Gobo Index (Low)  |
| 10             | Gobo Mode         |
| 11             | Control Channel   |
| 12             | Cyan (High)       |
| 13             | Cyan (Low)        |
| 14             | Yellow (High)     |
| 15             | Yellow (Low)      |
| 16             | Magenta (High)    |
| 17             | Magenta (Low)     |
| 18             | СТО               |
| 19             | Green Shift       |

# SQCC MODE

| DMX<br>CHANNEL | PARAMETER         |
|----------------|-------------------|
| 1              | Intensity (High)  |
| 2              | Intensity (Low)   |
| 3              | Strobe            |
| 4              | Color Preset      |
| 5              | Zoom              |
| 6              | Focus (High)      |
| 7              | Focus (Low)       |
| 8              | Gobo Index (High) |
| 9              | Gobo Index (Low)  |
| 10             | Gobo Mode         |

# SOCC MODE

| DMX<br>CHANNEL | PARAMETER         |
|----------------|-------------------|
| 1              | Intensity (High)  |
| 2              | Intensity (Low)   |
| 3              | Strobe            |
| 4              | Color Preset      |
| 5              | Zoom              |
| 6              | Focus (High)      |
| 7              | Focus (Low)       |
| 8              | Gobo Index (High) |
| 9              | Gobo Index (Low)  |
| 10             | Gobo Mode         |
| 11             | Control Channel   |
| 12             | Red (High)        |
| 13             | Red (Low)         |
| 14             | Green (High)      |
| 15             | Green (Low)       |
| 16             | Blue (High)       |
| 17             | Blue (Low)        |
| 18             | Amber (High)      |
| 19             | Amber (Low)       |
| 20             | Lime (High)       |
| 21             | Lime (Low)        |
| 22             | Cyan (High)       |
| 23             | Cyan (Low)        |

### **COMPLIANCE**

This equipment has been tested and found to comply with the limits for a Class A digital device pursuant to Part 15 of FCC Rules. These limits are designed to provide reasonable protection against harmful interference when this equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with Vari-Lite system, service, and safety guidelines, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference, in which case the user will be required to correct the interference at his/her own expense.

#### **DECLARATION OF CONFORMITY**

We declare, under our sole responsibility, that this product complies with the relevant clauses of the following standards and harmonized documents:

#### SAFETY

EN 60598-1:2015 + A1:2018;

EN 60598-2-17:2018;

EN 60598-2-4:2018;

EN 62493:2015;

EN 62471:2008:

EN 62031: 2008 + A1: 2013 + A2: 2015;

EN 61347-2-11:2001:

EN 61347-1:2015 Low Voltage Directive 2014/35/EU

#### **EMC**

EN 55032:2015

EN 55103-2: 2009

EN 61000-3-2:2014

EN 61000-3-3:2013

EN 55015:2013+A1:2015

EN 61547:2009

EMC Directive 2014/30/EU

#### ROHS

EN 62321:2012

We certify that the product conforms to the protection requirements of council directives: Low Voltage Directive 2014/35/EU, 2014/30/EU (EMC), and Restriction of the use of certain Hazardous Substances in electrical and electronic equipment Directive (RoHS), 2015/863. Equipment referred to in this declaration of conformity was first manufactured in 2017 in compliance with these standards.

#### **CUSTOMER SERVICE**

If you have any questions regarding this product, please contact Customer Service at +1-214-647-7880 or via e-mail at **entertainment.service@signify.** 

#### **LIMITED 2-YEAR WARRANTY**

Vari-Lite offers a two-year limited warranty on its control products against defects in materials or workmanship from the date of delivery. A copy of Vari-Lite two-year limited warranty containing specific terms and conditions can be obtained from the Vari-Lite website at <a href="https://www.strandlighting.com">www.strandlighting.com</a> or by contacting your local Vari-Lite office.

# SAFETY WARNINGS AND NOTICES

When using electrical equipment, basic safety precautions should always be followed including the following:

#### READ AND FOLLOW ALL SAFETY INSTRUCTIONS.

- · For indoor, dry locations use only. Do not use outdoors.
- Equipment should be mounted in locations and at heights where it will not readily be subjected to tampering by unauthorized personnel.
- The use of accessory equipment not recommended by the manufacturer may cause an unsafe condition.
- · Not for residential use. Do not use this equipment for other than intended use.
- Refer service to qualified personnel.
- The use of accessory equipment not recommended by the manufacturer may cause an unsafe condition.
- Not for residential use. Do not use this equipment for other than intended use.
- Refer service to qualified personnel. This fixture contains no user serviceable parts.
- Prior to first use, carefully inspect unit for damage from shipping.
  Installation and operation to be performed by qualified personnel only.
- · Use safety tether when mounting.
- Install only in locations with adequate ventilation of at least 50cm clearance from adiacent surfaces.
- · Ensure sure that ventilation slots are not blocked.
- Ensure that the voltage and frequency of the power supply match the power requirements of the fixture.
- The fixture must be earthed/grounded to the appropriate conductor.
- Do not operate fixture outside the ambient temperature range of 0-40°C.
- Do not connect the fixture to any dimmer pack.
- New fixtures may emit a chemical odor due to the manufacturing process. This
  odor will dissipate over time.
- Note distance requirement(s) from combustible materials or illuminated objects.
   Do not mount near gas or electric heaters.
- Prior to each use, carefully inspect power cables and replace any damaged cables.
- Exterior surfaces of the luminaire will be hot during operation. Take appropriate precautions.
- Continuous use of the fixture may shorten the lifespan. Power down the fixture when not in use.
- · Clean fixtures regularly, particularly when working in a dusty environment.
- · Never touch power cables or wires while the fixture is powered on.
- Avoid entangling power wires with other cables.
- In the event of a serious operating problem, immediately discontinue using the fixture.
- Never turn on and off the unit time after time.
- The housing, lenses, and/or the ultraviolet filter must be replaced if they are damaged.
- Disconnect mains power if the fixture is not used for a long time.
- Original packing materials can be reused for transporting the fixture.
- This fixture is designed for dry locations only. Exposure to rain or moisture may damage fixture unless it is suitably IP rated.
- Do not look directly at the LED light beam while the fixture is on.
- Equipment should be mounted in locations and at heights where it will not readily be subjected to tampering by unauthorized personnel.

# SAVE THESE INSTRUCTIONS.

**WARNING:** Refer to National Electrical Code® and local codes for cable specifications. Failure to use proper cable can result in damage to equipment or danger to personnel



# **AMERICAS**

10911 Petal Street Dallas, TX 75235 Tel: +1 214-647-7880 Fax: +1 214-647-8039

# ASIA

Room 1201, Freetown Tower D E 3rd Ring Rd S, 58 Chaoyang Qu Beijing Shi, China Tel: +8610-58674776 Fax: +8610-58674775

B-1-27, Dataran Cascades, No. 13A Jalan PJU 5/1 Kota Damansara PJU 5 47810 Petaling Jaya Selangor, Malaysia Tel: +60 3-7611 7302

# **EUROPE**

Rondweg Zuid 85 Winterswijk 7102 JD Netherlands Tel: +31 543-542516 Fax: +31 543-542513

24 Sovereign Park Coronation Road Park Royal, London NW10 7QP United Kingdom

Tel: +44 020 8965 3209

© 2020 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.