

Miro Cube® 2 4C & 4CA

DESIGNED BY THE BLACK TANK



PHOTOMETRICS

4C (RGBW)

All LEDs On Native

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	21,764 LUX	0.2 M	0.4 M
2.0M	5,441 LUX	0.4 M	0.8 M
3.0M	2,418 LUX	0.7 M	1.3 M
4.0M	1,360 LUX	0.9 M	1.7 M
5.0M	870 LUX	1.1 M	2.1 M
6.0M	604 LUX	1.3 M	2.5 M

■ Beam Angle: 12° ■ Field Angle: 23°

All LEDs On 20°

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	5,243 LUX	0.4 M	0.9 M
2.0M	1,310 LUX	0.9 M	1.7 M
3.0M	582 LUX	1.3 M	2.6 M
4.0M	327 LUX	1.7 M	3.5 M
5.0M	209 LUX	2.1 M	4.3 M
6.0M	145 LUX	2.6 M	5.2 M

■ Beam Angle: 24° ■ Field Angle: 45°

All LEDs On 40°

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	2,157 LUX	0.7 M	1.6 M
2.0M	539 LUX	1.5 M	3.2 M
3.0M	239 LUX	2.2 M	4.8 M
4.0M	134 LUX	3.0 M	6.4 M
5.0M	86 LUX	3.7 M	8.0 M
6.0M	59 LUX	4.4 M	9.6 M

■ Beam Angle: 40° ■ Field Angle: 77°

All LEDs On 60°

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	1,755 LUX	0.9 M	1.7 M
2.0M	438 LUX	1.8 M	3.3 M
3.0M	195 LUX	2.8 M	5.0 M
4.0M	109 LUX	3.7 M	6.7 M
5.0M	70 LUX	4.6 M	8.4 M
6.0M	48 LUX	5.5 M	10.1 M

■ Beam Angle: 50.0° ■ Field Angle: 80°

All LEDs On Native

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	21,704 LUX	0.2 M	0.4 M
2.0M	5,426 LUX	0.4 M	0.8 M
3.0M	2,411 LUX	0.6 M	1.2 M
4.0M	1,356 LUX	0.8 M	1.6 M
5.0M	868 LUX	1.0 M	2.0 M
6.0M	602 LUX	1.2 M	2.4 M

■ Beam Angle: 12° ■ Field Angle: 23°

All LEDs On 20°

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	4,540 LUX	0.4 M	0.8 M
2.0M	1,135 LUX	0.8 M	1.7 M
3.0M	504 LUX	1.3 M	2.5 M
4.0M	283 LUX	1.7 M	3.3 M
5.0M	181 LUX	2.1 M	4.1 M
6.0M	126 LUX	2.5 M	5.0 M

■ Beam Angle: 24° ■ Field Angle: 45°

All LEDs On 40°

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	1,803 LUX	0.7 M	1.5 M
2.0M	450 LUX	1.5 M	3.0 M
3.0M	200 LUX	2.2 M	4.5 M
4.0M	112 LUX	3.0 M	6.0 M
5.0M	72 LUX	3.7 M	7.5 M
6.0M	50 LUX	4.4 M	9.0 M

■ Beam Angle: 40° ■ Field Angle: 77°

All LEDs On 60°

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	1,416 LUX	0.9 M	1.6 M
2.0M	354 LUX	1.8 M	3.2 M
3.0M	157 LUX	2.8 M	4.7 M
4.0M	88 LUX	3.7 M	6.3 M
5.0M	56 LUX	4.6 M	7.9 M
6.0M	39 LUX	5.5 M	9.5 M

■ Beam Angle: 50.0° ■ Field Angle: 80°