

PHOTOMETRICS

WNC (2700-6000K Tunable White)

All On - No Lens Optic

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	24,281 LUX	0.3 M	0.7 M
2.0M	6,070 LUX	0.7 M	1.4 M
3.0M	2,697 LUX	1.0 M	2.2 M
4.0M	1,517 LUX	1.4 M	2.9 M
5.0M	971 LUX	1.7 M	3.6 M
6.0M	674 LUX	2.1 M	4.2 M

 Beam Angle: 20°
  Field Angle: 40°

Full Cool White - No Lens Optic

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	16,505 LUX	0.4 M	0.7 M
2.0M	4,126 LUX	0.7 M	1.5 M
3.0M	1,833 LUX	1.1 M	2.2 M
4.0M	1,031 LUX	1.4 M	2.9 M
5.0M	660 LUX	1.8 M	3.6 M
6.0M	458 LUX	2.1 M	4.2 M

 Beam Angle: 20°
  Field Angle: 40°

Full Warm White - No Lens Optic

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	10,952 LUX	0.3 M	0.7 M
2.0M	2,738 LUX	0.7 M	1.4 M
3.0M	1,216 LUX	1.0 M	2.1 M
4.0M	684 LUX	1.4 M	2.8 M
5.0M	438 LUX	1.7 M	3.5 M
6.0M	304 LUX	2.1 M	4.2 M

 Beam Angle: 20°
  Field Angle: 40°

Full Neutral White - No Lens Optic

Illuminance at a Distance

	Center Beam LUX	Beam Width	Field Width
1.0M	12,984 LUX	0.3 M	0.7 M
2.0M	3,246 LUX	0.7 M	1.4 M
3.0M	1,442 LUX	1.0 M	2.1 M
4.0M	811 LUX	1.4 M	2.8 M
5.0M	519 LUX	1.7 M	3.5 M
6.0M	360 LUX	2.1 M	4.2 M

 Beam Angle: 20°
  Field Angle: 40°