VARI*LITE

VL800 EVENTPROFILE



The Vari-Lite VL800 EVENTPROFILE is a compact LED event profile fixture that has the DNA of Vari-Lite built in. This high output framing profile luminaire offers full CYM+CTO color mixing and the signature "Vari-Lite smooth" movement that designers expect. The VL800 EVENTPROFILE includes professional-grade features in a small, tour-ready form factor, supplying a fixed color wheel; static and rotating gobo wheels; and prism, frost, and iris. With camera-ready frequency adjustment options and multi-mode fan control, the VL800 EVENTPROFILE is ready for any application.



FEATURES AND BENEFITS

- Cost-effective, high output LED profile built by Vari-Lite affordable LED framing profile from a brand you trust.
- Full CMY-CTO color mixing variable color mixing with saturation control, offering numerous vivid and creative color options
- Static and rotating gobo wheels, prism, frost, and iris professional features in a small form factor. Multiple visual options for a variety of uses.
- Multi-mode fan control adjust settings to control fan noise. Offers a low dB experience across all frequencies, eliminating buzzing or hums from an otherwise quiet device. Mode options include standard, studio, and whisper mode.
- Adjustable frequency to exceed camera frame rates camera friendly fixtures for IMAG or live televised events

SOURCE				
SOURCE	_		. = 0	
	Туре		LED	
	Wattage		350W	
OPTICAL	PERFORMANCE			
		Boost	17,000	
	Output lumens	Standard	13,000	
	Studio		10,000	
	Output CRI Output CCT		76	
			6500K	
			LUX*	FOOT-CANDLES*
	Narrow @ 5m		27300	2537
	Wide @ 5m		4060	645
	Narrow @ 10m		6900	378
	Wide @ 10m		480	49
	*All measurements taken in Standard mode		n Standard mode	
BEAM				
	Angle		8-40°	
	Angle		8-40°	



IMAGING				
	Gobo wheel 1	7 interchange glass gobos	s, fully rotating / indexable	
	Gobo wheel 2	8 fixed gobos	8 fixed gobos	
	Framing shutters 4 blade, continuous wipe shutter 45°+/- rota control of entire assembly			
	Iris	16 leaf		
	Prism 1 x 3 facet circular prism			
	Frost	30° medium		
COLORS	SYSTEM			
	Color mixing	Variable CMY		
	сто	Variable		
	Fixed color wheel	6 + open		
MOVEME	NT			
	Max pan angle	540°		
	Max tilt angle	270°		
NOISE LEVELS (BASE LEVEL 18.6db)				
	1m Full operation	Boost mode	48 dB	
	Full output db.	Standard mode	43.6 dB	
	Fan on continuous	Studio mode	37.8 dB	
	Standby	3m Idle - Full output db		
	Fan preset modes	Boost, standard, studio	Boost, standard, studio	
	Fan run mode	On (Continuous) / Auto	ito	
	Additional fan control*	Variable fan speed channe *standard mode only	el	
USER IN	TERFACE			
	Туре	4-button color LCD		
POWER				
	Range	100-240V @ 50/60Hz		
	Power in / thru	In and Out		
	Connector type	Neutrik TrueOne		
	Wattage (max)	575W		
DATA CONNECTIONS				
	DMX (RDM)	16-Bit Enhanced (45) 16-Bit (40) Clone (35)		
	Ethernet	ArtNet Streaming ACN		



PHYSICALS				
	IP rating Finish		IP20	
			Black	
DIMENSIO	ONS (H x W x L)		mm	in
	Fixture only		624 x 375 x 408	25 x 15 x 16
	Packed dimensio	ns	720 x 470 x 385	28 x 19 x 15
	Hanging centers		420	16.5
	Hanging type		107mm Omega clamps	
WEIGHT		kg	lb	
	Fixture only		21	46.3
	Packed weight	Net	25	55
		Gross	29	64
WARRANTY & APPROBATIONS				
	Warranty Approval / listings		2 years	
			CE, ETL, UL, FCC CSA, RoHS, ISO 9001	

PRODUCT NAME

VL800 EVENTPROFILE, LED Profile

91200545005


VL800 EVENTPROFILE, LED Profile (includes omega clamp and power input connector)

VARI*LITE

VL800 EVENTPROFILE


GOBO WHEEL 1 - rotating

 Night sky Circle of Ovals Bricked out Neurons Swirl Cross bars On the rocks Open 		_
3 Bricked out 4 Neurons 5 Swirl 6 Cross bars 7 On the rocks	1	Night sky
 4 Neurons 5 Swirl 6 Cross bars 7 On the rocks 	2	Circle of Ovals
5 Swirl 6 Cross bars 7 On the rocks	3	Bricked out
6 Cross bars 7 On the rocks	4	Neurons
7 On the rocks	5	Swirl
	6	Cross bars
8 Open	7	On the rocks
	8	Open





GOBO WHEEL 2 - fixed

1	Leafy breakup
2	Honeycomb
3	Radial breakup
4	Grid
5	Circle of dots
6	Punchcard
7	Vertical bars
8	Medium circle
9	Open









©2020 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Ref: 91200545005-100-v00