# **Reversible Module**

# **HDMI** to **HDBaseT**

XVVRM-HDMI2HDBT

HDBT —



(A) starting point





The HDMI to HDBaseT Reversible Module fits in the 8-Bay Reversible Rackmount Converter system.

heatrixx

The module can be inserted in the 8-Bay Frame in either direction, allowing the inputs/outputs to be positioned either at the front or the back of the unit depending on the application. There are no exposed PCBs as all modules are enclosed, and therefore protected against static shock, dust and general wear and tear. Gold-plated, redundant spring pins with magnetic retention deliver DC power to the modules, meaning no messy cabling and external power bricks are needed.

# Specifications

#### **Connections**

Video Input 1 x HDMI 1.4 with locking system

**Ethernet Port** 1 x 1 Gbps Ethernet on Neutrik EtherCON

Video Output 1 x HDBaseT 1.0 on shielded EtherCON

connector

**Recommended Cable** UTP CAT6a with EtherCON connectors

\*Contact Theatrixx for more info

# **Supported Signals**

**Video Format Support** HDMI 1.4 **HDCP Compliance** HDCP 1.4 **Ethernet Support** 100 Mpbs

### **Physical Specifications**

Height 121.5 mm (4.78 in) Depth 225 mm (8.85 in) Width 41 mm (1.61 in) Weight 710 g (1.56 lbs)

**Alternate Form Factor** Also available as a standalone converter

## **Environmental Specifications**

**Relative Humidity** 0% to 90% non-condensing

**Operating Temperature** 0-40 °C

## **Power Requirements**

Reversible redundant power fed by XVVRF8 **Power Supply** 

(8-Bay Rackmount Frame)

**Power Consumption** 20W

Voltage Range 12VDC

#### In the Box

Theatrixx Reversible Module HDMI to HDBaseT

## **Certifications & Compliance**

This device complies with the following international standards









# Ordering Information

XVVRM-HDMI2HDBT ...... Theatrixx Reversible Module HDMI to HDBaseT

XVVRF8 ...... Theatrixx 8-Bay Reversible Frame

XVVRM-BLANK ...... Theatrixx Blank Module